

Name: **Mexon OözyX EP NLGI 0, 1, 2, 3**

DESCRIPTION

MEXON OözyX EP Grease are high quality EP grease for industrial and automotive applications. Mexon EP Grease contain mineral base oil, lithium soap, EP [Extreme Pressure] additives, rust and oxidation inhibition which provide good lubrication and protection.

BENEFITS

- The operating temperature range is from -20°C to 130°C
- Protects against rust and corrosion.
- Long service life.
- Suitable for use in construction equipment bearings.
- Excellent structural stability.
- Protect against high load and tolerance to heat and water.

APPLICATION

It is recommended for automotive and industrial use such as ball joint, water pump bearing, wheel bearings, plane and rolling bearing.

TYPICAL TEST RESULT

Test Items	RESULTS			
	0	1	2	3
NLGI Consistency	0	1	2	3
Thickener Type	Lithium	Lithium	Lithium	Lithium
Color	Amber	Amber	Amber	Amber
Worked Penetration at 25 °C, 1/10 mm	360	320	270	230
Dropping Point °C	201	210	208	211
4-Ball Wear	0.42	0.42	0.45	0.51
4-Ball EP, Weld Load Kg _f	251	251	251	251

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of Mexon Lubricants products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with Mexon Lubricants technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

Made in South Korea

