

Name: **Mexon OözyX MP NLGI 2, 3**

DESCRIPTION

MEXON OözyX MP Grease is high graded multi-purpose grease which is lithium thickener, base on mineral oil. Particularly suitable for industrial work and automotive chassis components, wheel bearings, clutch bearings and many other kinds of bearing operating under heavy duty engines.

BENEFITS

- The operating temperature range is from -20°C to 130°C- Long service life.
- Protects against rust and corrosion.
- Long service life.
- Moly provides lubrication even if base grease is squeezed out.
- Excellent structural stability.

APPLICATION

It is recommended for automotive and industrial use such as ball joint, water pump bearing, wheel bearings.

TYPICAL TEST RESULT

Test Items	RESULTS	
	2	3
NLGI Consistency	2	3
Thickener Type	Lithium	Lithium
Color	Amber	Amber
Worked Penetration at 25 °C, 1/10 mm	275	235
Dropping Point °C	226	215
4-Ball Wear	0.49	0.53
4-Ball EP, Weld Load Kg _f	205	205

Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of Mexon Lubricants products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with Mexon Lubricants technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

Made in South Korea

